IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of Docket No: Q64029

Massimo BRIOSCHI, et al.

Appln. No.: 09/833,666 Group Art Unit: 2616

Confirmation No.: 1733 Examiner: Richard CHANG

Filed: April 13, 2001

For: METHOD AND APPARATUS FOR AUTOMATIC DELAY COMPENSATION IN

SPACE DIVERSITY RADIO TRANSMISSIONS

AMENDMENT UNDER 37 C.F.R. § 1.116

MAIL STOP AF

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

the accompanying pages.

Sir:

In response to the Office action dated November 1, 2006, and further to the Request For Reconsideration filed this same date, please amend the above-identified application as follows on

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

 (Currently Amended) A method of compensating for a possible delay between two or more radio transmission paths in space diversity radio transmissions, said method comprises:

receiving a first analog signal;

receiving at least one second analog signal;

sampling said first analog signal and said at least one second analog signal to obtain a first digital signal and at least one second digital signal, respectively, a possible delay being present between the first digital signal and the at least one second digital signal; and

sending said digital signals to respective equalizers;

delaying, in a digital manner, eitherone of said first and second digital signal or said at least one second digital signals relative to the other by a period equal to an integer multiple of the sampling period, said delaying comprising automatically calculating a value of said integer multiple, and optionally

recovering, at equalization, the difference between the imposed delay and the real delay.

(Previously Presented) A method according to claim 1, wherein delaying comprises calculating the value of the integer multiple, wherein calculating the integer multiple comprises; realizing delayed replicas $r_{1j}(kT_{ss}) = s_1(kT_{ss} - jT_{ss})$ and $r_{2j}(kT_{ss}) = s_2(kT_{ss} - iT_{ss})$ of said first and said at least second digital signals, with $0 \le j \le N_1$ and $0 \le i \le N_2$, N_1T_{ss} being the maximum assumable delay of the first signal with respect to the at least one second signal and N_2T_{ss} being the maximum assumable delay of the at least one second signal with respect to the first signal;

calculating cross-correlations

$$\begin{split} &xc_{1j} = E \bigg\{ \sum_{m} \sum_{n} a_{n} a_{m} * g_{2} * \big(kT_{ss} - mT \big) g_{1} \big(kT_{ss} - nT - \tau - jT_{ss} \big) \bigg\} \text{ with } 0 \leq j \leq N_{1}, \\ &xc_{2j} = E \bigg\{ \sum_{m} \sum_{n} a_{m} a_{n} * g_{1}^{*} \big(kT_{ss} - nT - \tau \big) g_{2} \big(kT_{ss} - mT - iT_{ss} \big) \bigg\} \text{ with } 0 \leq i \leq N_{2}, \end{split}$$

between the various delayed replicated signals, where * denotes the complex conjugate operation and $E\{\cdot\}$ the time average operation; and

deriving the maximum value of said cross-correlations as i and j vary, namely $M = \max_{i,j} \left(|xc_{1j}|^p, |xc_{2i}|^p \right)$ said maximum value corresponding to the value of the integer multiple.

3. (Previously Presented) A method according to claim 2, wherein the method further comprises selecting the delayed replica to be sent to said equalizers as a function of the information related to the maximum of the calculated cross-correlations. 4. (Currently Amended) An apparatus for compensating a delay between two or more radio transmission lines in space diversity radio transmissions, said apparatus comprising: means for receiving a first analog signal;

means for receiving at least one second analog signal;

means for sampling the first analog signal and the at least one second analog signal to obtain a first digital signal and at least one second digital signal, respectively, a delay being possibly present between the first digital signal and the at least one second digital signal; and equalizers receiving said digital signals at their respective inputs:

means for delaying, in a digital manner, eitherone of said first and second digital signal or said at least one second digital signals relative to the other by a period equal to an integer multiple of the sampling period, said delaying comprising automatically calculating a value of said integer multiple, and

equalizer means capable of restoring the difference between an imposed delay and the real delay. 5. (Previously Presented) An apparatus according to claim 4, wherein said delay means comprise means for calculating the value of the integer multiple, wherein said calculation means comprise:

means for realizing delayed replicas $r_{ij}(kT_{sa}) = s_i(kT_{sa} - jT_{sa})$ and $r_{2i}(kT_{sa}) = s_2(kT_{sa} - iT_{sa})$ of said first and said at least one second digital signals, with $0 \le j \le N_1$ and $0 \le i \le N_2$, N_1T_{sa} being the maximum assumable delay of the first signal with respect to the at least one second signal and N_2T_{sa} being the maximum assumable delay of the at least one second signal with respect to the first signal;

means for calculating cross-correlations

$$xc_{1j} = E\left\{\sum_{m}\sum_{n}a_{n}a_{m} * g_{2} * (kT_{su} - mT)g_{1}(kT_{su} - nT - \tau - jT_{su})\right\} \text{ with } 0 \le j \le N_{1},$$

$$xc_{2j} = E\left\{\sum_{m}\sum_{n}a_{m}a_{n} * g_{1}^{*}(kT_{su} - nT - \tau)g_{2}(kT_{su} - mT - iT_{su})\right\} \text{ with } 0 \le i \le N_{2}$$

between the various delayed replicated signals, where * denotes the complex conjugate operation and $E_{Y}^{\{\}}$ the time average operation; and

means for deriving a maximum value of said cross-correlations as i and j vary, namely $M = \max_{i,j} \left\| x c_{1j} \right\|^p, \left| x c_{2i} \right|^p \right), \text{ said maximum value corresponding to the value of the integer}$ multiple.

- 6. (Previously Presented) An apparatus according to claim 5, further comprising switching means for selecting a proper delayed replica to be sent to said equalizer means as a function of information related to the maximum of the cross-correlations calculated.
- 7. (Previously Presented) A computer program comprising computer program code means adapted to perform the method claimed in claim 1 when said program is run on a computer.
- 8. (Previously Presented) A computer-readable medium having a program recorded thereon, said computer-readable medium comprising computer program code means adapted to perform the method claimed in claim 1 when said program is run on a computer.
- 9. (Currently Amended) An apparatus for compensating a delay between two or more radio transmission lines in space diversity radio transmissions, said apparatus comprising:
 - a first receiver that receives a first analog signal;
 - a second receiver that receives at least one second analog signal;
- a sampling circuit that samples the first analog signal and the at least one second analog signal to obtain a first digital signal and at least one second digital signal, respectively, a delay being possibly present between the first digital signal and the at least one second digital signal;
 - equalizers that receive said digital signals at their respective inputs;
- a digital delay circuit that digitally delays either one of said first and second digital signal or said at least one second digital signal relative to the other by a period equal to an

integer multiple of the sampling period, said delaying comprising automatically calculating a value of said integer multiple, and

a restoring equalizer that restores the difference between an imposed delay and the real delay.

10. (Previously Presented) An apparatus according to claim 9, wherein said digital delay circuit comprises a calculation circuit for calculating the value of the integer multiple, wherein said calculation circuit:

a delay circuit that realizes delayed replicas $r_{ij}(kT_{sa}) = s_1(kT_{sa} - jT_{sa})$ and $r_{2i}(kT_{sa}) = s_2(kT_{sa} - iT_{sa})$ of said first and said at least one second digital signals, with $0 \le j \le N_1$ and $0 \le i \le N_2$, N_1T_{sa} being the maximum assumable delay of the first signal with respect to the at least one second signal and N_2T_{sa} being the maximum assumable delay of the at least one second signal with respect to the first signal;

a correlation circuit that calculates cross-correlations

$$xc_{ij} = E\left\{\sum_{m}\sum_{n}a_{n}a_{m} * g_{2} * (kT_{ss} - mT)g_{1}(kT_{ss} - nT - \tau - jT_{ss})\right\} \text{ with } 0 \le j \le N_{1},$$

$$xc_{2i} = E\left\{\sum\sum_{m}\sum_{n}a_{m}a_{n} * g_{1}^{*}(kT_{ss} - nT - \tau)g_{2}(kT_{ss} - mT - iT_{ss})\right\} \text{ with } 0 \le i \le N_{2}$$

between the various delayed replicated signals, where * denotes the complex conjugate operation and $E\{\cdot\}$ the time average operation; and

a maximum value circuit derives a maximum value of said cross-correlations as i and j vary, namely $M = \max_{i,j} \left(|xc_{1j}|^p, |xc_{2i}|^p \right)$, said maximum value corresponding to the value of the integer multiple.

11. (Previously Presented) An apparatus according to claim 10, further comprising a switch for selecting a proper delayed replica to be sent to said restoring equalizer as a function of information related to the maximum of the cross-correlations calculated.

Amendment Under 37 C.F.R. § 1.116 USSN 09/833,666

REMARKS

Claims 1-11 remain in the application, the claims having been amended to more clearly

define the invention. Reconsideration of the application and allowance of all claims are

respectfully requested in view of the following remarks.

The invention defined in the claims without the above amendments is believed to

patentably distinguish over the applied art for the reasons set forth in detail in the Request For

Reconsideration filed this same date. The above amendments are made to further emphasize the

distinctive nature of the invention, by incorporating into claim 1 a portion of the subject matter

of allowable claim 2, i.e., that the delaying step involves the calculation of the appropriate delay.

This concept I neither shown nor suggested in the applied art.

Entry of the amendment is respectfully requested in that it simply clarifies the distinctive

feature of the invention pointed out in the remarks of the response to the previous Office action,

i.e., that the delay is variable, as it must be in order to compensate for a delay amount which is

unknown from the outset.

Further examination and allowance are respectfully requested.

Respectfully submitted,

SUGHRUE MION, PLLC Telephone: (202) 293-7060

Facsimile: (202) 293-7860

WASHINGTON OFFICE
23373
CUSTOMER NUMBER

Date: February 1, 2007

David J. Cushing Registration No. 28,703

Registration No. 28,70.

9

1485552	
09833666	
1733	
Method and apparatus for automatic delay compensation in space diversity radio transmissions	
Massimo Brioschi	
23373	
David J. Cushing	
Q64029	
01-FEB-2007	
13-APR-2001	
23:28:47	
Utility	

Payment information:

Submitted with Payment	no	
------------------------	----	--

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)	Multi Part /.zip	Pages (if appl.)
1		Q64029Amendment3.pdf	99230	yes	9

	Document Description	Start	End		
	Supplemental Response or Supplemental Amendment	1	1		
	Claims	2	8		
	Applicant Arguments/Remarks Made in an Amendment	9	9		
/arnings:	arnings:				
nformation	formation:				

Multipart Description/PDF files in .zip description

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card. as described in MPEP 503.

Total Files Size (in bytes):

99230

New Applications Under 35 U.S.C. 111

W In

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.